

Anybus X-gateway - AS-Interface Master - PROFINET-IO Device

Item number: AB7648-F

The Anybus X-gateway AS-Interface Master to PROFINET IO Device enables you to connect any AS-Interface device or equipment to PROFINET IO control systems. It can be used when there is no existing AS-Interface control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



A protocol converter that connects AS-Interface devices to PROFINET-IO PLCs

Features and benefits

✓ Reach new markets

Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.

✓ Slim hardware design

The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

✓ Easy configuration – No programming required!

Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.

✓ Trusted partner

Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.



✓ No PLC card slot needed

The gateway does not use a card slot in the control system, leaving room for other equipment.

✓ 3-year warranty

The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.

✓ Increased PLC performance

The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.

✓ Life cycle management

HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

Anybus X-gateway - AS-Interface Master - PROFINET-IO Device



General

Net Width (mm)	44
Net Height (mm)	127
Net Depth (mm)	114
Net Weight (g)	420
Packed Width (mm)	155
Packed Height (mm)	75
Packed Depth (mm)	200
Packed Weight (g)	600
Operating Temperature °C Min	-25
Operating Temperature °C Max	65
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Current Consumption Type Value at Vcc Nom (mA)	200mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	400mA @ 24V DC
Input Voltage (V)	24V DC (-20% to +20%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE

Anybus X-gateway - AS-Interface Master - PROFINET-IO Device



General

Mounting	DIN-rail (EN 50022 standard)
Housing Materials	Aluminium, Plastic
Packaging Material	Cardboard

Identification and Status

Product ID	AB7648-F
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	5A991.b.1

Physical Features

Connectors / Input / Output	2x RJ45, USB-B Config port
Contains Battery	No

PROFINET Features

PROFINET Mode	Slave
PROFINET Supported Functionality	Soft Real-Time (RT); Max 64 slots / 1 sub-slot; DCP support; Acyclic Data exchange
PROFINET Configuration File	GSDML available
PROFINET Bandwidth	10/100Mbit full/half duplex down to 1ms
PROFINET Input Data Size	512 bytes
PROFINET Output Data Size	512 bytes

Certifications and Standards

Protection Class IP	IP20
RoHS Compliant	Yes
Recycle / Disposal	TRUE

Anybus X-gateway - AS-Interface Master - PROFINET-IO Device



Certifications and Standards	
Product Certifications	CE, UL, WEEE, RoHS
UL Information	E214107: Ord.Loc UL508, CSA C22.2 NO. 142
Environment	EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
WEEE Category	IT and telecommunications equipment