

## Anybus X-gateway – Interbus FO Slave - PROFINET-IO Device

Item number: AB7657-F

The Anybus X-gateway Interbus FO Slave to PROFINET-IO Device enables you to connect any Interbus FO system to any PROFINET-IO control system. Anybus gateways ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects Interbus FO and PROFINET-IO control systems*

### Features and benefits

- ✓ **Reach new markets**  
Target new markets using different protocols without needing to change your hardware or software, thereby decreasing your time to market and development costs.
- ✓ **Slim hardware design**  
The gateway is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Easy configuration – No programming required!**  
Quickly establish the connection between the two networks with the included Anybus Configuration Manager software. No programming skills are required for the setup process.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.
- ✓ **No PLC card slot needed**  
The gateway does not use a card slot in the control system, leaving room for other equipment.
- ✓ **3-year warranty**  
The gateway is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Increased PLC performance**  
The gateway allows for fast transfer of cyclic I/O data between the two networks, offloading your PLC from working with additional calculations.
- ✓ **Life cycle management**  
HMS maintains every part of the gateway, including network updates, throughout the product's lifecycle.

# Anybus X-gateway – Interbus FO Slave - PROFINET-IO Device



| General                                        |                                    |
|------------------------------------------------|------------------------------------|
| Net Width (mm)                                 | 44                                 |
| Net Height (mm)                                | 127                                |
| Net Depth (mm)                                 | 114                                |
| Net Weight (g)                                 | 400                                |
| Packed Width (mm)                              | 17                                 |
| Packed Height (mm)                             | 9                                  |
| Packed Depth (mm)                              | 19                                 |
| Packed Weight (g)                              | 600                                |
| Operating Temperature °C Min                   | -25                                |
| Operating Temperature °C Max                   | 65                                 |
| Storage Temperature °C Min                     | -40                                |
| Storage Temperature °C Max                     | 85                                 |
| Current Consumption Type Value at Vcc Nom (mA) | 200mA @ 24V DC                     |
| Current Consumption Max value at Vcc nom (mA)  | 400mA @ 24V DC                     |
| Input Voltage (V)                              | 24V DC (-20% to +20%)              |
| Power Connector                                | 2-pin, 5.08 Phoenix plug connector |
| Reverse Polarity Protection                    | Yes                                |
| Short Circuit Protection                       | Yes                                |
| Isolation                                      | TRUE                               |

# Anybus X-gateway – Interbus FO Slave - PROFINET-IO Device



## General

|                    |                              |
|--------------------|------------------------------|
| Mounting           | DIN-rail (EN 50022 standard) |
| Housing Materials  | Aluminium, Plastic           |
| Packaging Material | Cardboard                    |

## Identification and Status

|                                                                       |            |
|-----------------------------------------------------------------------|------------|
| Product ID                                                            | AB7657-F   |
| Country of Origin                                                     | Sweden     |
| HS Code                                                               | 8517620000 |
| Dual Usage                                                            | No         |
| Export Control Classification Number (ECCN) (Applies only to the U.S) | 5A991.b.1  |

## Physical Features

|                             |                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------|
| Connectors / Input / Output | 2x RJ45, 1x HFBR-2505C and 1x HFBR-1505C Fiber Optic network connectors, USB-B Config port |
| Contains Battery            | No                                                                                         |

## INTERBUS Features

|                                  |                                                                                                                                                                                                                                   |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| INTERBUS Mode                    | Slave                                                                                                                                                                                                                             |
| INTERBUS Supported Functionality | EN 50170; Fiber Optic conform to IEC874-2 and DIN47258; Transmission Media: Plastic fibre, core 980um, clad 1000um: HCS (glass) fibre, core 200um, clad 230 um;PCP V.2.0. (0, 1, 2, or 4 words);Automatic slave address detection |
| INTERBUS Baud Rate               | 500 kbit/s – 2 Mbit/s                                                                                                                                                                                                             |
| INTERBUS Input Data Size         | 20 bytes of process data (512 bytes with PCP                                                                                                                                                                                      |
| INTERBUS Output Data Size        | 20 bytes of process data (512 bytes with PCP                                                                                                                                                                                      |

## PROFINET Features

|                                  |                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------|
| PROFINET Mode                    | Slave                                                                              |
| PROFINET Supported Functionality | Soft Real-Time (RT); Max 64 slots / 1 sub-slot; DCP support; Acyclic Data exchange |
| PROFINET Configuration File      | GSDML available                                                                    |
| PROFINET Bandwidth               | 10/100Mbit full/half duplex down to 1ms                                            |

# Anybus X-gateway – Interbus FO Slave - PROFINET-IO Device



## PROFINET Features

|                           |           |
|---------------------------|-----------|
| PROFINET Input Data Size  | 512 bytes |
| PROFINET Output Data Size | 512 bytes |

## Certifications and Standards

|                        |                                                                                                                                          |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Protection Class IP    | IP20                                                                                                                                     |
| RoHS Compliant         | Yes                                                                                                                                      |
| Recycle / Disposal     | TRUE                                                                                                                                     |
| Product Certifications | CE, UL, WEEE, RoHS                                                                                                                       |
| UL Information         | E214107: Ord.Loc UL508, CSA C22.2 NO. 142                                                                                                |
| Environment            | EN 61000-6-4, EN 55016-2-3 Class A, EN 55022 Class A, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6 |
| WEEE Category          | IT and telecommunications equipment                                                                                                      |