

## VGA over IP Extender Transmitter over Cat5/Cat6, RS-232 Serial and IR Control, 1920 x 1440 (1080p), 328 ft. (100 m), TAA

MODEL NUMBER: **B160-001-VSI**



Converts VGA video + audio to an IP-based signal that is transmitted point-to-point to a receiver 328 ft. away via Cat5e/6 cable or through a dedicated Ethernet network switch.

### Features

#### Distributes VGA A/V, Serial and IR Control Signals over Cat5/6 Cabling

- Converts audio/video to an IP-based signal that is transmitted point-to-point to a display 328 ft. away
- Add low-cost network switches between transmitter and receiver to continue extending distance up to 328 ft. per switch
- HDMI output for connecting a local display

#### Create a Multi-In, Multi-Out Installation Using B160-Series Transmitters and Receivers

- Connect up to 64 transmitters and 255 receivers through multiple dedicated managed network switches
- IGMP-enabled switches allow centralized control over which sources show on which displays
- Video source can be sent to any analog or digital display, so you can mix and match technologies and use existing monitors

#### Enhanced Technical Features

- Supports video resolutions up to 1920 x 1440, including 1080p (limited to receiver's max resolution)
- Uses H.264 video compression standard
- Transmits on 20–60 kHz IR frequency
- Extends IR control signals that control a source from a remote display
- Supports RS-232 serial baud rates up to 57600 Bps
- HDCP and 3D compatible

#### Plug-and-Play Functionality

- No software or drivers required
- Hardware included for mounting on wall, rack or pole
- Compatible with all B160-Series A/V over IP receivers

### Highlights

- Compatible with B160-Series A/V over IP receivers
- Video source can be sent to any analog or digital display
- Supports video resolutions up to 1920 x 1440, including 1080p\*
- HDMI output on transmitter for connecting local display
- Plug and play—no software or drivers required

### Package Includes

- Transmitter unit
- External power supply (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V 2A)
- Plug adapters for U.S., U.K., Europe and Australia
- IR-Out cable
- 3.5 mm to DB9 adapter cable (M/F)
- Mounting hardware
- Owner's manual



Powering Business Worldwide

TRIPP LITE  
SERIES

**TAA-Compliant**

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW                                       |                                          |
|------------------------------------------------|------------------------------------------|
| UPC Code                                       | 037332196682                             |
| Product Type                                   | Transmitter                              |
| Technology                                     | IR; VGA/SVGA; A/V over IP; Cat5/5e; Cat6 |
| VIDEO                                          |                                          |
| Max Supported Video Resolution                 | 1920 x 1440 @ 60Hz                       |
| Max 720P Range (ft)                            | 328                                      |
| Max 1080P Range (ft)                           | 328                                      |
| Max 1280 x 720 (720p) Range (ft)               | 328                                      |
| Max 1920 x 1080 (1080p) Range (ft)             | 328                                      |
| Max 1920 x 1200 Range (ft)                     | 328                                      |
| Transmitter Video Input                        | VGA                                      |
| Transmitter - Number of Video Outputs          | 1                                        |
| Transmitter - Local Display Output             | HDMI                                     |
| Range Extension using other Tripp Lite product | 328ft                                    |
| Recommended Cabling                            | N202-Series Cat6 Patch Cable             |
| Other Tripp Lite product used to extend range  | network switch                           |
| Max Supported Color Depth                      | 24-bit True Color                        |
| HDR Support                                    | No                                       |
| 3D Video Supported                             | No                                       |
| Maximum Signal Range (ft)                      | 328                                      |
| Maximum Signal Range (m)                       | 100                                      |
| Maximum Signal Range Details                   | 328 ft via Cat6275 ft via Cat5e          |
| AUDIO                                          |                                          |
| Audio Input                                    | 3.5mm                                    |
| Audio Specification                            | Stereo Audio                             |
| INPUT                                          |                                          |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                                                                                                                                  |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Power Adapter Plug(s)                     | AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America                                                                                     |
| AC Power Adapter Input Specs (V / Hz / A)    | 100-240V / 50/60Hz / 1.0A                                                                                                                                        |
| AC Power Adapter Output Specs (V / A)        | 5V / 2A                                                                                                                                                          |
| AC Power Adapter Cord Length (ft.)           | 4.5                                                                                                                                                              |
| AC Power Adapter Cord Length (m)             | 1.4                                                                                                                                                              |
| Bus Powered                                  | No                                                                                                                                                               |
| <b>POWER</b>                                 |                                                                                                                                                                  |
| Power Source Type                            | AC Adapter                                                                                                                                                       |
| AC Plug Type                                 | NEMA 1-15P; BS1363; CEE 7/16 Schuko; AS/NZS 3112                                                                                                                 |
| Power Source                                 | Unit (Included)                                                                                                                                                  |
| Power Over Cable (PoC) Support               | No                                                                                                                                                               |
| DC Barrel Plug                               | OD: 5.5 x 2.1 x 7.5mm, Positive Pin, Negative Sleeve                                                                                                             |
| <b>CONNECTIONS</b>                           |                                                                                                                                                                  |
| Number of Ports                              | 1                                                                                                                                                                |
| Side A - Connector 1                         | 3.5MM (FEMALE); HD15 (FEMALE)                                                                                                                                    |
| Side B - Connector 1                         | HDMI (FEMALE); RJ45 (FEMALE)                                                                                                                                     |
| Daisy-chainable / Cascadable                 | No                                                                                                                                                               |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                                                                                                                                                  |
| LED Indicators                               | RJ45 Output (Green / Power, Orange / Signal), Channel Signal (Red), Power (Green)                                                                                |
| <b>PHYSICAL</b>                              |                                                                                                                                                                  |
| Color                                        | Black                                                                                                                                                            |
| Included Mounting Accessories                | Wallmount                                                                                                                                                        |
| Number of Displays                           | 1                                                                                                                                                                |
| Optional Mounting Accessory Notes            | Can DIN Mount using Tripp Lite Bracket <a href="https://tripplite.eaton.com/din-rail-mounting-bracket-for-digital-signage-version-2-B110-DIN-02">B110-DIN-02</a> |
| Form Factor/Mounting Options                 | Box; Wall-mount                                                                                                                                                  |
| Shipping Dimensions (hwd / in.)              | 2.00 x 6.40 x 10.20                                                                                                                                              |
| Shipping Dimensions (hwd / cm)               | 5.08 x 16.26 x 25.91                                                                                                                                             |
| Shipping Weight (lbs.)                       | 1.70                                                                                                                                                             |
| Shipping Weight (kg)                         | 0.77                                                                                                                                                             |
| Unit Dimensions (hwd / in.)                  | 0.000 x 0.000 x 0.000                                                                                                                                            |
| Unit Packaging Type                          | Box                                                                                                                                                              |
| Unit Weight (lbs.)                           | 0.2                                                                                                                                                              |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                                                                 |
|----------------------------------------------|-----------------------------------------------------------------|
| Unit Weight (kg)                             | 0.09                                                            |
| Housing                                      | Metal                                                           |
| <b>ENVIRONMENTAL</b>                         |                                                                 |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)                                       |
| Storage Temperature Range                    | 5° to 122°F (-15° to 50°C)                                      |
| Relative Humidity                            | 0% to 85%, Non-Condensing                                       |
| BTUs                                         | 18.1 BTU/Hr                                                     |
| <b>COMMUNICATIONS</b>                        |                                                                 |
| Max 1024 x 768 Range (ft)                    | 328                                                             |
| Max 480P Range (ft)                          | 328                                                             |
| Max 1440 x 900 Range (ft)                    | 328                                                             |
| Max 1080i Range (ft)                         | 328                                                             |
| Max 1920 x 1440 Range (ft)                   | 328                                                             |
| Max 480i Range (ft)                          | 328                                                             |
| Max 640 x 480 Range (ft)                     | 328                                                             |
| Max 800 x 600 Range (ft)                     | 328                                                             |
| Max 1600 x 1200 Range (ft)                   | 328                                                             |
| EDID Compatible                              | No                                                              |
| IR Remote Extension Support                  | Yes                                                             |
| RS-232 Serial Extension Support              | Yes                                                             |
| Consumer Electronics Control (CEC) Supported | No                                                              |
| USB Extension Support                        | No                                                              |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                                                                 |
| 10/100 Ethernet Extension Support            | No                                                              |
| Built-In Equalizer                           | No                                                              |
| Driver Required                              | No                                                              |
| <b>STANDARDS &amp; COMPLIANCE</b>            |                                                                 |
| External Power Supply Certifications         | BSMI; CB; CCC; CE; FCC; GS; PSE; RCM; TUV; UL; cUL              |
| Product Compliance                           | RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>                |                                                                 |
| Product Warranty Period (Worldwide)          | 1-year limited warranty                                         |



*Powering Business Worldwide*

TRIPP LITE  
SERIES

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.