

## 2-Port Mini DisplayPort to VGA Hub, DP1.2, TAA

MODEL NUMBER: **B155-002-VGA**



Converts and splits a Mini DisplayPort video signal for display on two VGA monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms.

### Description

The B155-002-VGA 2-Port Mini DisplayPort to VGA Splitter converts and splits a Mini DisplayPort video signal for display on two VGA-enabled monitors, projectors or televisions at the same time. Ideal for offices, conference rooms, retail settings, trade shows and classrooms, this compact splitter features a built-in Mini DisplayPort cable that connects to the source. It lets you use your existing VGA displays instead of buying new Mini DisplayPort monitors or docking stations.

The B155-002-VGA supports video resolutions up to 1080p @ 60 Hz (1920 x 1080), as well as HDCP, EDID and DDC. Orange LEDs next to each output port indicate whether the splitter is powered on and transmitting a signal to the connected displays. The splitter works with all operating systems and is small enough to carry in your backpack or computer bag. Plug-and-play convenience means no software or drivers are needed. An included USB Micro-B cable connects between the source and the splitter to provide power, so no external power supply is required.

### Features

**Converts and Splits Mini DisplayPort Signal to 2 VGA Displays Simultaneously** Ideal for offices, conference rooms, trade shows and classrooms  
**Built-in Mini DisplayPort cable** connects to source  
**Included USB Micro-B cable** supplies power to splitter  
**Save money** on new Mini DisplayPort displays or docking stations

**Top-Shelf Performance** Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080) Complies with HDCP, EDID and DDC  
**LEDs** indicate whether splitter is powered on and transmitting signal to connected displays

**Easy to Use Almost Anywhere** Works with all operating systems  
**Plug and play**—no software, drivers or external power supply required  
**Compact unit** fits easily in backpack or computer bag

### Highlights

- Supports video resolutions up to 1080p @ 60 Hz (1920 x 1080)
- Included USB Micro-B cable supplies power to unit
- Works with all operating systems
- Compact enough for easy carrying in backpack or laptop bag
- Plug and play—no software or drivers required

### Package Includes

- B155-002-VGA 2-Port Mini DisplayPort to VGA Splitter
- USB Micro-B cable, 3 ft.
- Owner's manual

## Specifications

| OVERVIEW     |              |
|--------------|--------------|
| UPC Code     | 037332191489 |
| Product Type | Splitter     |



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

|                                              |                                  |
|----------------------------------------------|----------------------------------|
| Technology                                   | DisplayPort; VGA/SVGA            |
| Host Connector                               | MINI DISPLAYPORT (FEMALE)        |
| <b>VIDEO</b>                                 |                                  |
| Max Supported Video Resolution               | 1920 x 1080 (1080p) @ 60Hz       |
| Max Supported Color Depth                    | 24-bit True Color                |
| 3D Video Supported                           | Yes                              |
| <b>AUDIO</b>                                 |                                  |
| Audio Specification                          | 2.0-channel surround sound audio |
| <b>POWER</b>                                 |                                  |
| Power Consumption (Watts)                    | 4.1                              |
| <b>CONNECTIONS</b>                           |                                  |
| Number of Ports                              | 2                                |
| Side A - Connector 1                         | MINI DISPLAYPORT (MALE)          |
| Side A - Connector 2                         | MICRO-USB B (FEMALE)             |
| Side B - Connector 1                         | (2) HD15 (FEMALE)                |
| Connector Plating                            | Nickel                           |
| Contact Plating                              | Gold                             |
| Input x Output                               | 1 x 2                            |
| Daisy-chainable / Cascadable                 | No                               |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                                  |
| LED Indicators                               | (x2) Orange (Monitor Signal)     |
| <b>PHYSICAL</b>                              |                                  |
| Color                                        | Black                            |
| Material of Construction                     | Polycarbonate                    |
| Cable Length (ft.)                           | 0                                |
| Cable Length (m)                             | 0.00                             |
| Rackmountable                                | No                               |
| Shipping Dimensions (hwd / in.)              | 7.90 x 5.60 x 1.70               |
| Shipping Dimensions (hwd / cm)               | 20.07 x 14.22 x 4.32             |
| Shipping Weight (lbs.)                       | 0.60                             |
| Shipping Weight (kg)                         | 0.27                             |
| Unit Dimensions (hwd / in.)                  | 3.000 x 2.400 x 1.000            |



Powering Business Worldwide



|                                      |                                                                 |
|--------------------------------------|-----------------------------------------------------------------|
| Unit Dimensions (hwd / cm)           | 7.6 x 6.15 x 2.55                                               |
| Unit Dimensions (hwd / mm)           | 61.5 x 76 x 25.5                                                |
| Unit Packaging Type                  | Box                                                             |
| Unit Weight (lbs.)                   | 0.154                                                           |
| Unit Weight (kg)                     | 0.07                                                            |
| <b>ENVIRONMENTAL</b>                 |                                                                 |
| Operating Temperature Range          | 14° to 167°F (10° to 75°C)                                      |
| Storage Temperature Range            | -4° to 176°F (-20° to 80°C)                                     |
| Relative Humidity                    | 0% to 85%, Non-Condensing                                       |
| BTUs                                 | 14 BTU/Hr                                                       |
| <b>COMMUNICATIONS</b>                |                                                                 |
| EDID Compatible                      | Yes                                                             |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                                                 |
| MST Support                          | No                                                              |
| Displayport Specification            | 1.2                                                             |
| HDCP Specification                   | 1.3                                                             |
| Driver Required                      | No                                                              |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                                                 |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA); Trade Agreements Act (TAA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                                                 |
| Product Warranty Period (Worldwide)  | 3-year limited warranty                                         |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.