



Anybus ProfiHub B2FO2+

Item number: 17220

The ProfiHub B2FO2+ is a cost-effective solution to link PROFIBUS fiber optic to multiple RS 485 segments and vice versa.



Simple network expansion over long distances

Features and benefits

- ✓ **Fiber optic to multi RS 485 Segments**
Enable network communication over long distances
- ✓ **Point-to-point, bus- and star configurations**
Create a robust network backbone through segmentation and redundancy
- ✓ **Cost-effective solution**
One device for network extension and segmentation

Anybus ProfiHub B2F02+



General

Net Width (mm)	129
Net Height (mm)	113
Net Depth (mm)	43
Net Weight (g)	592
Packed Width (mm)	16
Packed Height (mm)	6
Packed Depth (mm)	26
Packed Weight (g)	592
Operating Temperature °C Min	-25
Operating Temperature °C Max	70
Current Consumption Type Value at Vcc Nom (mA)	300 mA
Current Consumption Max value at Vcc nom (mA)	300 mA
Input Voltage (V)	9...31 VDC
Power Wire Diameter (mm)	< 2.5 mm ²
Reverse Polarity Protection	Yes
Warranty (years)	1 Year

Identification and Status

Product ID	17220
Country of Origin	Netherlands (the)
HS Code	8471800000



Anybus ProfiHub B2F02+

Identification and Status

Dual Usage	No
Export Control Classification Number (ECCN) (Applies only to the U.S)	EAR99

Physical Features

Contains Battery	No
------------------	----

Certifications and Standards

Protection Class IP	IP20
CE	Yes
FCC	Yes
UL	Yes
DNV	No
Waste Certification (WEEE)	No
WEEE Category	IT and telecommunications equipment