

Actuator

51-
701.006

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/component/51-701.006/...>

Your product:



51-701.006 Actuator

Loading . . .

FRONT

Front dimension: 24 mm x 18 mm

Front form: Rectangular

MOUNTING

Design: Raised

Mounting type: Panel mounting

ELECTRICAL CHARACTERISTICS

Switching voltage and switching current: 100 mA at 42 VAC/VDC

Electric strength: 2500 VAC, 50 Hz, 1 min. between all terminals and earth, according to IEC 61058-1, part 15

MECHANICAL CHARACTERISTICS

Terminal: Universal terminal, 2 x 0.5 mm

Tightening torque: Fixing nut max. 0.5 Nm

Weight: 0.006 kg

AMBIENT CONDITION


IP front protection:	IP65, according to DIN EN 60529
Operating temperature:	– 25 °C ... + 55 °C, mounted as a block, make sure the heat can escape freely
Storage temperature:	– 40 °C ... + 85 °C
Shock resistance:	15 g for 11 ms, as per DIN / EN 60512-4-3, DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal)

CERTIFICATE


REACH:	REACH compliant
RoHS:	RoHS compliant

OTHER

Short Description:	Actuator, 24 mm x 18 mm, Rectangular, Universal terminal, 2 x 0.5 mm, IP65, according to DIN EN 60529
Internal size:	21,5 mm x 15,3 mm
Housing colour:	Black
Wiring diagrams:	



Component layouts:



Technical drawing of a shaft-hub assembly. The drawing includes the following dimensions and tolerances:

- Shaft diameter: $\varnothing 16.2^{+0.2}_0$
- Hub inner diameter: $\varnothing 18^{+0.1}_0$
- Hub outer diameter: 18×24
- Hub length: $18 \times 18 / \varnothing 18$
- Shaft length: 18 min.
- Shaft diameter tolerance: 0 to $+0.2$
- Hub inner diameter tolerance: 0 to $+0.1$
- Hub length tolerance: 0 to $+0.1$
- Shaft length tolerance: 0 to $+0.1$

A = Solder terminal
B = Plug-in terminal 2.8 mm x 0.5 mm
C = Universal terminal 2.0 mm x 0.5 mm