



Powering Business Worldwide

TAA-Compliant 15-Amp DC Power Supply, 13.8VDC, Precision Regulated AC-to-DC Conversion

MODEL NUMBER: **PR15**



Highlights

- Smaller footprint maximizes operating space
- Crowbar overvoltage protection prevents damage to connected equipment due to overvoltages
- Automatic time-controlled overcurrent protection in case of overload
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchase

Provide precise DC power from an AC source with this compact and lightweight power supply. The PR15 efficiently converts 120 volts AC into 13.8 volts DC. It has a high power density that makes it ideal for a wide variety of applications, like 50 watt transmitters, VHF/UHF ham radios, low power linear amplifiers, test bench equipment, point-of-sale displays, and aquariums.

Description

Precision regulated DC power supplies are ideal for commercial/land-mobile, ham and CB radios, test bench supplies, base stations, tape players and amplifiers. Designed for years of reliable service and superior performance, they efficiently convert 120 volts AC into 13.8 volts DC (+/-0.5V). The Trim Line Series of DC power supplies offers a low-profile design with a footprint that matches the most popular radios on the market, such as Motorola, Radius, GE Monogram Series and EF Johnson models.

Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Features

- Smaller footprint maximizes operating space
- Crowbar overvoltage protection prevents damage to connected equipment due to overvoltages
- Current-limiting electronic foldback enables time-controlled automatic overcurrent protection in case of overload
- Solid state, integrated circuit maintains excellent regulation of output voltage
- Regulated output voltage maintains up to 95% of no load value
- High quality filtering creates very low ripple/low noise operation
- Heavy-duty power transformer provides complete isolation from noise on incoming AC power
- Large heat sinks and vented cabinets supply cool operation for continuous use and long life of the unit
- Illuminated on/off switch
- Connectors: Hardwire terminals / Red positive (+), Black negative (-)
- Working Temperature Range: 0° C to 40° C (32° F to 104° F), 0 to 95% humidity, non-condensing
- Storage Temperature Range: -15° C to 50° C (5° F to 122° F)



Powering Business Worldwide

- LED Indicators: Red LED indicates that DC output is being provided

Specifications

OVERVIEW	
UPC Code	037332060020
OUTPUT	
Intermittent (Peak) Amps	15
PHYSICAL	
Shipping Dimensions (hwd / in.)	5.00 x 7.12 x 13.50
Shipping Dimensions (hwd / cm)	12.70 x 18.10 x 34.29
Shipping Weight (lbs.)	13.15
Shipping Weight (kg)	5.96
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
Unit Dimensions (hwd / cm)	11.43 x 15.24 x 25.4
Unit Weight (lbs.)	13
Unit Weight (kg)	5.90
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	1-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.