

8 Series Pushbutton Switches

■ Features

1. Contacts

Silver or gold-plated contacts.

2. Epoxy resin case

UL94V-0 self-extinguishing epoxy.

3. Actuator style

Over 30 actuator variations.

4. Insulation between terminal and ground: 4 mm minimum.

5. Prevention of flux entry

The epoxy resin seal on bottom of the switch helps prevent the entry of solder and flux.

6. Insulation barrier:



Insulation barrier design between poles helps prevent short-circuiting between poles ensuring high reliability.

■ Specifications

Rating	Max. rating	6A 125 VAC/3A 250 VAC/4A 30 VDC(Resistive load)	
Initial contact resistance	10 mΩ max. (1A 2~4 VDC)		
Initial dielectric strength	1,500 VAC 1 minute		
Initial insulation resistance	1,000 MΩ min. (500 VDC)		
Electrical life (Excluding 8R & 8W)	Alternate type	40,000 operations	
	Momentary type	25,000 operations	
Operating temperature range	-30°C~+85°C		
Storage temperature range	-40°C~+85°C		

(Excluding 8R & 8W.)


■ Terminal Styles

Solder(Style:1)	PC Straight(Style:2)
t=0.8 	t=0.8 

8 Series Pushbutton Switches Selection Table

Part No.	Name	Actuator shape	Number of poles	Switching function	Terminal style	Page
8N	Standard Pushbutton		1.2.3.4	ON - ON ON - (ON)	  S/D P/C Solder Straight	239
8P	Splash Proof Pushbutton		1.2	ON - ON ON - (ON)	 S/D Solder	242
8Y	Mustang Pushbutton		1.2.3	ON - ON ON - (ON)	 S/D Solder	245
8R-N	Soft Touch Pushbutton		1.2	ON - ON ON - (ON)	  S/D P/C Solder Straight	248
8W-N	Snap-in Pushbutton		1.2	ON - (ON)	  S/D P/C Solder Straight	251

Part Numbering



8Y

Mustang Pushbutton Switches

RoHS Compliant




Features

The 8Y series is a sub-miniature pushbutton switch with a larger, rugged actuator and a larger bushing. Suitable for applications where panel space is limited and a larger actuator is needed.


Table of Part Numbers

Terminal style	No. of pole		1 pole	2 poles	3 poles
	Switching function				
Solder Lug	ON	- ON	8Y1011-Z	8Y2011-Z	8Y3011-Z
	ON	- (ON)	8Y1021-Z	☆ 8Y2021-Z	★ 8Y3021-Z

Panel Cut-Out Dimensions



Terminal Styles



Standard Accessories

《Supplied with switch》

Hex Nut	Lockwasher	Locking Ring
140008010243	140008030055	140008020067
Nickel plated	Zinc plated	Zinc plated

Optional Accessories


《Sold separately》

Color Cap		
Dimensions	Color	Part No.
Gloss finish 	White	140000470023
	Red	140000470052
	Black	140000470051
Vinyl chloride resin		





● Specify the Color Cap by part number if Color Cap is desired.

Color Cap Mounting

Snap in the color button on to the actuator.



SPDT






Switching function		
Part No.		
※8Y1011-Z	ON	ON
8Y1021-Z	ON	(ON)
Connecting terminals	2-3	2-1

※ : The circuit switches each time the switch button is pressed.

S/D

Terminal numbers are not shown on the switch.

DPDT






Switching function		
Part No.		
※ 8Y2011-Z	ON	ON
☆8Y2021-Z	ON	(ON)
Connecting terminals	2-3 5-6	2-1 5-4

※ : The circuit switches each time the switch button is pressed.

S/D

Terminal numbers are not shown on the switch.

3PDT



Switching function		
Part No.		
※ 8Y3011-Z	ON	ON
★8Y3021-Z	ON	(ON)
Connecting terminals	2-3 5-6 8-9	2-1 5-4 8-7

※ : The circuit switches each time the switch button is pressed.

S/D

Terminal numbers are not shown on the switch.

■Precautions

1. Soldering Specifications

(1) Manual soldering

Device : Solder iron

① 420°C Max. 3 sec. Max.

(2) Auto soldering

② 275°C ±10°C 5 sec. Max.

The above-stated soldering conditions shall apply only to switches with straight terminals. Auto soldering is not possible with right-angle terminals. Switches with right-angle terminals should be soldered manually according to the conditions specified in (1) above.

(3) When putting the switches through an aging process after they were soldered onto the printing board or after installed into a complete end product, be sure to remove the buttons of the switches.

2. Mounting

- Do not bend the terminals before mounting the switch on the PC board.
- After mounting the switch, do not place the device in such a way that the device weight will be applied on to the actuator of the switch.
- For switches with straight terminals, solder the switch on the PC board after fixing the switch on the panel with a nut.

3. Flux Cleaning

- (1) Solvent : Fluorine or Alcohol type.
- (2) 8 series are not washable. To wash the PC board, clean the soldering surface of the PC board with a brush so that the switch is not exposed to the cleaning solution.

■Packaging Specification

Perforated Plastic Bag

25 pcs./pack

