

Foot Operated Switches Series

Special Purpose Switches



7792



7792-01



7792-03

Description

Littelfuse Foot Operated Switches are designed for universal applications within harsh environments. Their mounting, body, and actuator features are designed for ease-of-use and extended product life cycle.

These switches are designed to provide controlled circuit closure, traditionally for head lamp applications. Equipped with a large actuator interface these switches are designed for repeated use.

Specifications

Positions:	2 Positions: Off-On
Sprint Return:	Spring Return to Off

Applications

- Construction Equipment
- Agricultural Equipment
- Material Handling Equipment
- Transit and Commercial Vehicles

Web Resources

Download technical resources at:
littelfuse.com/foot-operated-switches

Ordering Information

PART NUMBERS			DESCRIPTION	CIRCUITRY	HOUSING	MOUNTING	INGRESS PROTECTION	ACTUATOR	TERMINATION
BULK	BOX	RETAIL							
7792	—	7792-BP	Normally Open Water-Resistant Foot Operated Push Button Switch	SPST	Diecast Steel	Surface Mount through 3 ¼" (6.35mm)- 20 Panel Holes	Hencol Sealed Body	Steel Plunger	2 Screw
7792-01	7792-01-BX	7792-01-BP	Normally Open Foot Operated Push Button Switch	SPST	Diecast Steel	Surface Mount through 3 ¼" (6.35mm)- 20 Panel Holes	None; Moisture-Resistant	Steel Plunger	2 Blade
7792-03	7792-03-BX	7792-03-BP	Normally Open Water-Resistant Foot Operated Push Button Switch	SPST	Plated Steel	Surface Mount through 2 ¼" (6.35mm)- 20 Panel Holes	Hencol Sealed Body	Steel Plunger	2-16AWG leads terminated in Atpiv #12010973