

Product data sheet

Specifications



Disconnect switch, TeSys VLS, additional pole, early-make closing, 40A, for 16A to 40A switch, size 1, DIN rail

VLS1P040R1E

⚠ Discontinued on: Dec 18, 2023

⚠ Discontinued

Main

Range	TeSys
Device short name	VLS1P
Product or component type	Additional pole
Performance level	High performance
Poles description	1P
Contacts type and composition	1 NO
Contact operation	Early make
Range compatibility	TeSys TeSys VARIO LS VLS3P
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes

Complementary

Mounting location	Left Right
Mounting support	DIN rail
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	40 A (at 131 °F (55 °C))
[Ithe] conventional enclosed thermal current	40 A
[Ie] rated operational current	40 A AC-21A Ue: 400 V 40 A AC-21A Ue: 500 V 40 A AC-21A Ue: 690 V 40 A AC-22A Ue: 400 V 40 A AC-22A Ue: 500 V 40 A AC-22A Ue: 690 V 40 A AC-23A Ue: 400 V 25 A AC-23A Ue: 500 V 25 A AC-23A Ue: 690 V 40 A Ue: 600 V UL 508
Rated operational power in W	18.5 kW 400 V AC-23A) 18.5 kW 500 V AC-23A) 22 kW 690 V AC-23A)
Intermittent duty class	Class 120 - 60 %
Making capacity (I Rms)	60 A 690 V AC-21A 120 A 690 V AC-22A 400 A 690 V AC-23A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Icm] rated short-circuit making capacity	1128 A 690 V
[Icw] rated short-time withstand Rms current	800 A 690 V 1 s
Rated conditional short-circuit current	50 kA 400 V 40 A gG
Breaking capacity	60 A 690 V AC-21A) 120 A 690 V AC-22A) 320 A 690 V AC-23A)
Mechanical durability	100000 cycles
Electrical durability	100000 cycles AC-21A
Connections - terminals	Power circuit screw clamp terminals 0.02 in² (10 mm²) solid Power circuit screw clamp terminals 0.02 in² (16 mm²) flexible - without cable end
Tightening torque	Power circuit 15.9...17.7 lbf.in (1.8...2 N.m) screw clamp terminals
Height	3.07 in (78 mm)
Width	0.5 in (12 mm)
Depth	1.7 in (43.6 mm)
Product weight	0.09 lb(US) (0.04 kg)
Colour	Grey

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3
Product certifications	cULus GL
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.3 in (3.3 cm)
Package 1 Width	3.50 in (8.89 cm)
Package 1 Length	3.00 in (7.62 cm)
Package 1 Weight	0.11 lb(US) (0.05 kg)
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	5.9 in (15 cm)
Package 2 Width	5.9 in (15 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	3.340 lb(US) (1.515 kg)

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins