

Product data sheet

Specifications



Disconnect switch, TeSys VLS,
additional neutral terminal, for 30A
to 125A, size 2 (70mm), DIN mount

VLS1NR2

⚠ Discontinued on: Dec 18, 2023

⚠ Discontinued

Main

Range	TeSys
Device short name	VLS1N
Product or component type	Additional neutral block
Performance level	High performance
Poles description	1N
Contacts type and composition	Without
Range compatibility	TeSys TeSys VARIO LS VLS3P TeSys TeSys VARIO LS VLS1P TeSys TeSys VARIO LS VLSA TeSys TeSys VARIO LS VLS1G
Network type	AC
Network frequency	50/60 Hz

Complementary

Mounting location	Right Left
Main device mounting mode	DIN rail
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	125 A (at 131 °F (55 °C))
[Ithe] conventional enclosed thermal current	125 A
Connections - terminals	screw clamp terminals 0.08 in² (50 mm²) solid screw clamp terminals 0.1 in² (70 mm²) flexible - without cable end
Tightening torque	44.3...53.1 lbf.in (5...6 N.m) screw clamp terminals
Height	3.9 in (100 mm)
Width	0.9 in (23 mm)
Depth	1.9 in (48.6 mm)
Product weight	0.24 lb(US) (0.11 kg)
Colour	Grey

Environment

Standards	UL98 CSA C22.2 No 4 IEC 60947-3
-----------	---------------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	cULus GL
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Fire resistance	1760 °F (960 °C) IEC 60695-2-11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.9 in (10.0 cm)
Package 1 Width	0.9 in (2.3 cm)
Package 1 Length	1.73 in (4.39 cm)
Package 1 Weight	4.0 oz (113.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	10.540 lb(US) (4.781 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins