





SPECIFICATIONS:

CONTACT RATING: 3A @ 125 VAC OR 28 VDC (RESISTIVE)
 INITIAL CONTACT RESISTANCE: 20 MILLIOHMS MAXIMUM
 INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM @ 500 VDC.
 DIELECTRIC STRENGTH: 1000 VOLTS RMS AT SEA LEVEL
 LIFE EXPECTANCY: 10,000 CYCLES AT FULL RATED LOAD
 CONTACTS: SOLID SILVER
 SEAL-TOGGLE: PER MIL-S-83731A
 STATIC: PARAGRAPH 4.8.20
 DYNAMIC: PARAGRAPH 4.8.20


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
D	0G3C-0194-05	27MAR07	MZ



PANEL CUTOUT



SINGLE POLE



DOUBLE POLE

TTE23P-8T 1/4	2 TO 1 5 TO 4	OFF	2 TO 3 5 TO 6
TTF23N-8T 1/4	2 TO 1 5 TO 4	NONE	2 TO 3 5 TO 6
TTF13F-8T 1/4	2 TO 1	OFF	2 TO 3
TTF13D-8T 1/4	2 TO 1	NONE	2 TO 3
SWITCH NO.	FLAT	FLAT	FLAT

TERMINALS CONNECTED WHEN TOGGLE IS IN POSITION SHWN

NOTE: TERMINAL DESIGNATION NUMBERS ARE FOR REFERENCE ONLY AND DO NOT APPEAR ON SWITCHES NOS 4, 5, 6 FOR D.P. VERSION ONLY.

AUGAT D/N 40210

THIRD ANGLE PROJECTION




DISTRIBUTION

1	2	3	4	5	6	7	8	9	10
---	---	---	---	---	---	---	---	---	----

INSPECT PER
ALCO QAS 100

SYMBOL



A.Q.L.
CRITICAL
MAJOR
MINOR

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES
 TOLERANCES ON:
 3 PL. DECIMALS ± .010
 ANGLES ±
 FRACTIONS

SURF

SIGNATURES

DRAWN
CHECKED
ENGRG
ISSUED

DATE

DATE

tyco
Electronics

CUSTOMER DRAWING - TOGGLE SWITCH

SEALED SP & DP
TTE13(*)-8T 1/4

SIZE: SC NO.

SCALE 4/1

DWG. NO.

1437563-6

REV

D

SHEET OF 1