

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples



Check Inventory



1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Features

- Large B constant for high temperature sensing capability
- Designed for high density
- Available in standard EIA compatible case size
- Internal electrode designed for enhanced reliability
- Excellent aging stability

Applications

- Battery pack temperature sensing
- Power Supply and Power Electronics Thermal Monitoring
- Consumer electronics thermal management.
- Appliance temperature control.
- Motor winding protection.
- Industrial equipment and power electronics monitoring.

Electrical Specifications

Part Number	Resistance		B Constant 25/50		Maximum Operating Current	Thermal Time Constant	Thermal Dissipation Factor	Rated Power
Test Condition	25°C		25°C, 50°C		25°C	25°C	25°C	25°C
Units	kΩ	±%	Kelvin	±%	mA	seconds	mW/°C	mW
Symbol	R25	Δ	β	□	I _{max}	τ	δ	P _{max}
ABNTC-0603-472Δ-3950□	4.7	H, J, K	3950	H	0.46	< 5	1.0	100
ABNTC-0603-502Δ-3950□	5.0	H, J, K	3950	H	0.44			
ABNTC-0603-682Δ-3950□	6.8	F, H, J, K	3950	F, H	0.38			
ABNTC-0603-103Δ-3450□	10	F, H, J, K	3450	F, H	0.31			
ABNTC-0603-103Δ-3950□	10	F, H, J, K	3950	F, H	0.33			
ABNTC-0603-153Δ-3950□	15	H, J, K	3950	F, H	0.25			
ABNTC-0603-223Δ-4050□	22	F, H, J, K	4050	H	0.21			
ABNTC-0603-333Δ-4050□	33	F, H, J, K	4050	F, H	0.17			
ABNTC-0603-473Δ-4150□	47	F, H, J, K	4150	F, H	0.14			
ABNTC-0603-503Δ-4150□	50	F, H, J, K	4150	F, H	0.13			
ABNTC-0603-683Δ-4150□	68	F, H, J, K	4150	F, H	0.12			
ABNTC-0603-104Δ-4250□	100	F, H, J, K	4250	F, H	0.10			

Operating Temperature: -55°C to +125°C

Storage: Temperature 10°C to +50°C, RH<75%

Test Conditions:

Unless otherwise specified, the standard atmospheric conditions for measurement/test as:

- a. Ambient Temperature: 20±15°C
- b. Relative Humidity: 65±20%
- c. Air Pressure: 86 kPa to 106 kPa

ABNTC-0603 Series is RoHS/RoHS II Compliant and Pb free

MSL level = 1



12117 Bee Caves Rd, Bldg-3, Suite 200
Bee Cave, TX 78738
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION D : 7/16/2026

ABRACON IS
ISO9001-2015
CERTIFIED

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples




Check Inventory



1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Electrical Characteristics Curve



Resistance vs. Temperature

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples




Check Inventory



1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Electrical Characteristics Curve



Resistance vs. Temperature

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples




Check Inventory




1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Materials



	Part Name	Material
1	Base Material	MnO
2	Internal Conductor	Ag-Pd
3	Terminal Electrode	Ag (Inner layer) Ni-Sn (Outer layer)

Part Number Identification



Part Marking

No Marking

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples





Check Inventory



1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Mechanical Specifications



Series	L	W	T	a	A	B	C
ABNTC-0603	1.6±0.15	0.8±0.15	0.8±0.15	0.3±0.2	0.60~0.80	0.60~0.80	0.60~0.80

Dimensions: mm

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples




Check Inventory



1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Reflow Profile



Zone	Description	Temperature	Times
1	Preheat	$T_{SMIN} \sim T_{SMAX}$ 150°C ~ 200°C	60 ~ 120 sec.
2	Reflow	T_L ≥217°C	60 ~ 90 sec.
3	Peak heat	T_P 260°C Max.	10 sec. MAX

Ref Paste: Sn/3.0Ag/0.5Cu (Lead-Free)

Max ramp up rate: 3°C/Sec

Max ramp down rate: 6°C/Sec

Maximum reflows: 2

Sensing Thermistor (NTC-Chip)



ABNTC-0603

Request Samples




Check Inventory




1.6 x 0.8 x 0.8 mm
RoHS/RoHS II Compliant
MSL Level = 1

Packaging

Tape & Reel: 4,000 pcs/reel



A	B	P	T (max)
1.0 ± 0.2	1.8 ± 0.2	4.0 ± 0.1	1.1



Dimensions: mm

ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf (COTS, which are designed, intended and validated for use in commercial, industrial and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



12117 Bee Caves Rd, Bldg-3, Suite 200
Bee Cave, TX 78738
Phone: 512-371-6159 Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISION D : 7/16/2026

ABRACON IS
ISO9001-2015
CERTIFIED