







- NOTES:
1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0
TERMINALS - HIGH PERFORMANCE COPPER ALLOY
 2. FINISH: 30µIN SELECTIVE GOLD IN CONTACT AREA, SELECTIVE TIN
ON PCB TAILS, NICKEL OVERALL.
 3. REFER TO MOLEX PRODUCT SPEC PS-76060-999 FOR PERFORMANCE SPECIFICATIONS
AND ADDITIONAL PCB INFORMATION.
 4. EACH SIGNAL WAFER CONTAINS 2 COLUMNS OF TERMINALS.
 5. PRODUCT IS PACKAGED PER PK-70873-591.
 6. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPEC PS-45499-002.
 7. REFER TO MOLEX SALES DRAWING SD-76165-001 FOR THE MATING HEADERS AND
SD-76410-001 FOR THE MATING RAM CONNECTORS.
 8. REFER TO MOLEX PCB ROUTING GUIDE AS-76060-990 FOR ANTIPAD AND ROUTING
RECOMMENDATIONS.
 9. PART NUMBER 76170-1020 SHOWN ON DRAWING. KEYING FEATURES WILL CHANGE
WITH COLUMN SIZE.
 10. MINIMUM BOARD THICKNESS IS 1.00 mm FOR COMPLIANT PIN FUNCTIONALITY.
 11. MARKING: LOCATED APPROXIMATELY AS SHOWN. PART NUMBER AND DATE CODE.

DAUGHTERCARD HOLE PATTERN (CONNECTOR SIDE)

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
DIMENSION UNITS		SCALE	CURRENT REV DESC: CORRECTED TOLERANCE TYPO IN TITLE BLOCK				molex IMPACT 100 OHM DC 3 PAIR SIGNAL MODULE UNGUIDED SALES DRAWING							
MM		NTS												
GENERAL TOLERANCES (UNLESS SPECIFIED)														
ANGULAR TOL		±					0.5°							
4 PLACES		±												
3 PLACES		±		PRODUCT CUSTOMER DRAWING										
2 PLACES		±	0.130											
1 PLACE		±	0.25	STATUS: Production		DRWN: Rohith V		2026-06-09		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
0 PLACES		±		CHK'D: Yogeesh BC		2026-06-11		2026-07-01		SD-76170-001		PSD	001	E6
APPR: Chetan CV				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER		SHEET NUMBER	
				C-SIZE		76170		SEE CHART		GENERAL MARKET		1 OF 2		

MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH $\varnothing$
76170-*006	6	18	11.40	9.50	0.46±0.05
76170-*008	8	24	15.20	13.30	
76170-*010	10	30	19.00	17.10	
76170-*016	16	48	30.40	28.50	
76170-*036	6	18	11.40	9.50	0.39±0.05
76170-*038	8	24	15.20	13.30	
76170-*020	10	30	19.00	17.10	
76170-*026	16	48	30.40	28.50	

76170-*0**

1 = OPEN LEAD-FREE

OF COLUMNS
06 = 6 COL 0.46 PTH
08 = 8 COL 0.46 PTH
10 = 10 COL 0.46 PTH
16 = 16 COL 0.46 PTH
20 = 10 COL 0.39 PTH
26 = 16 COL 0.39 PTH
36 = 6 COL 0.39 PTH
38 = 8 COL 0.39 PTH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: CORRECTED TOLERANCE TYPO IN TITLE BLOCK			molex IMPACT 100 OHM DC 3 PAIR SIGNAL MODULE UNGUIDED SALES DRAWING		
MM	NTS						
GENERAL TOLERANCES (UNLESS SPECIFIED)							
ANGULAR TOL	± 0.5°						
4 PLACES	±	STATUS: Production DRWN: Rohith V CHK'D: Yogeesh BC APPR: Chetan CV	2026-06-09 2026-06-11 2026-07-01	PRODUCT CUSTOMER DRAWING			
3 PLACES	±			DOCUMENT NUMBER			
2 PLACES	± 0.130			SD-76170-001			
1 PLACE	± 0.25			DOC TYPE	DOC PART	REVISION	
0 PLACES	±			PSD	001	E6	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			C-SIZE	76170	SEE CHART	GENERAL MARKET	2 OF 2