

# 42U SmartRack Value Series Standard-Depth Rack Enclosure Cabinet, 2400 lbs (1088.6 kgs) Capacity with doors & side panels

MODEL NUMBER: SR2400



## Features

- Ships fully assembled for rapid deployment and rolls into place on heavy-duty pre-installed casters (casters are removable)
- Front and rear sets of equipment mounting rails accommodate all standard 19-inch rackmount equipment and adjust in 1/4" increments. Adjustment is quick and convenient. The easy-view depth index ensures consistent rail placement without requiring time-consuming measurements.
- Toolless mounting brackets allow quick installation of compatible PDUs and vertical cable managers. Each rack can accommodate two vertical PDUs
- Rack Enclosure includes mounting hardware of 50 pieces of M6 cage nuts and 50 pieces of M6 screws
- Tough textured powder coat finish resists conditions found in non-IT environments such as warehouses
- Massive front-to-rear ventilation capacity. 65+% open space in door perforation pattern meets or exceeds server manufacturer requirements
- Maximum usable internal depth of 37 inches/94 cm (front to rear rail)
- Weight ratings of 2400 lbs (1088.6 kgs) stationary and 1600 lbs (725.7 kgs) rolling
- Front door is locking, reversible and removable
- Rear doors are locking and reversible. Split rear door design reduces clearance requirements for service entry allowing the enclosure to be placed closer to a wall
- Locking removable side panels are 'half size' to make them smaller and lighter improving ease of installation and servicing. Two side panels per side (4 panels total). Side panels are keyed alike to the front and rear doors.
- Built in baying tabs allow enclosures to be combined securely in rows. Center-to-center width can be set at 600mm or 24" to match standard data center floor tiles
- Leveling feet extend to allow enclosure to be positioned on uneven floors. Levelers are removable
- Compact design allows the enclosure to roll through standard height commercial doorways
- Convenient grounding system. All components are grounded to the enclosure frame which includes multiple connections for facility ground. Front and rear doors include quick-release ground wires.
- Open bottom for cable access
- Top panel has generous cable access holes. Panel can be removed toollessly in seconds without having to disconnect cables first
- Stabilizing brackets are used for shipment and can be reattached at the bottom of the enclosure frame

## Highlights

- Standard 24" (600mm) width and 42" (1050mm) depth for optimal use of floor space
- Accommodates all standard 19-inch rackmount equipment
- Ships fully assembled
- 2400 lbs (1088.6 kgs) stationary / 1600 lbs (725.7 kgs) rolling load capacity
- Locking, removable, reversible front and rear doors
- Locking, removable side panels keyed alike with doors
- Pre-installed casters and leveling feet
- Rolls through a standard 80" tall doorway
- Meets all rack enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance

## Package Includes

- SR2400 Rack Value Series Rack Enclosure Cabinet
- (4) side panels
- (4) side panel locks
- (2) door & side panel keys
- (50) M6 screws
- (50) M6 washers
- (50) M6 cage nuts
- Owner's Manual



Powering Business Worldwide



on the inside or outside of the rack

- Meets all enclosure requirements towards PCI DSS (Payment Card Industry Data Security Standard) Compliance
- Compatible with airflow optimization and cable management accessories

## Specifications

| OVERVIEW                            |                                          |
|-------------------------------------|------------------------------------------|
| UPC Code                            | 037332183736                             |
| Device Compatibility                | Patch Panel; Network Switch; UPS; Server |
| Rack Type                           | Enclosure                                |
| PHYSICAL                            |                                          |
| Color                               | Black                                    |
| Rack Height                         | 42U                                      |
| Rack Depth                          | Standard                                 |
| Factory Preset Rack Depth (in.)     | 27.75                                    |
| Factory Preset Rack Depth (cm)      | 70.5                                     |
| Factory Preset Rack Depth (mm)      | 705                                      |
| Maximum Device Depth (cm)           | 93.98                                    |
| Maximum Device Depth (in.)          | 37                                       |
| Maximum Device Depth (mm)           | 940                                      |
| Minimum Device Depth (cm)           | 10.16                                    |
| Minimum Device Depth (in.)          | 4                                        |
| Minimum Device Depth (mm)           | 102                                      |
| Shipping Dimensions (hwd / in.)     | 85.00 x 26.00 x 45.00                    |
| Shipping Dimensions (hwd / cm)      | 215.90 x 66.04 x 114.30                  |
| Shipping Weight (lbs.)              | 328.00                                   |
| Shipping Weight (kg)                | 148.78                                   |
| Unit Dimensions (hwd / in.)         | 78.500 x 23.630 x 43.000                 |
| Unit Dimensions (hwd / cm)          | 199.39 x 60.02 x 109.22                  |
| Unit Weight (lbs.)                  | 260                                      |
| Unit Weight (kg)                    | 117.93                                   |
| Weight Capacity - Rolling (kg)      | 726                                      |
| Weight Capacity - Rolling (lbs.)    | 1600                                     |
| Weight Capacity - Stationary (kg)   | 1,089                                    |
| Weight Capacity - Stationary (lbs.) | 2400                                     |



Powering Business Worldwide



|                                      |                            |
|--------------------------------------|----------------------------|
| Number of Vertical Mounting Rails    | 4                          |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                            |
| Grounding Details                    | Front and back door frames |
| Built-in Cable Management            | Yes                        |
| Pre-Installed Casters                | Yes                        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                            |
| Product Certifications               | UL 60950-1                 |
| Product Compliance                   | RoHS; CE (Europe); UKCA    |
| <b>WARRANTY &amp; SUPPORT</b>        |                            |
| Product Warranty Period (Worldwide)  | 5-year limited warranty    |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.