

12	11	10	9	8	7	6	5	4	3	2	1																								
FACE VIEW-MALE INSERT					B1 <table><tr><th>MATERIAL NUMBER</th><th>ENGINEERING NUMBER</th><th>POLES</th><th>FINISHED LENGTH</th></tr><tr><td>1300130090</td><td>1R2007A20A120</td><td>2</td><td>12 IN [1FT]</td></tr><tr><td>1300130248</td><td>1R3007A20F020</td><td>3</td><td>2FT [0.6M]</td></tr><tr><td>1300130387</td><td>1R4007A20F060</td><td>4</td><td>6FT [1.8M]</td></tr><tr><td>1300130536</td><td>1R5007A20F030</td><td>5</td><td>3FT [0.9M]</td></tr><tr><td>1300131009</td><td>1R6007A20F030</td><td>6</td><td>3FT [0.9M]</td></tr></table>							MATERIAL NUMBER	ENGINEERING NUMBER	POLES	FINISHED LENGTH	1300130090	1R2007A20A120	2	12 IN [1FT]	1300130248	1R3007A20F020	3	2FT [0.6M]	1300130387	1R4007A20F060	4	6FT [1.8M]	1300130536	1R5007A20F030	5	3FT [0.9M]	1300131009	1R6007A20F030	6	3FT [0.9M]
MATERIAL NUMBER	ENGINEERING NUMBER	POLES	FINISHED LENGTH																																
1300130090	1R2007A20A120	2	12 IN [1FT]																																
1300130248	1R3007A20F020	3	2FT [0.6M]																																
1300130387	1R4007A20F060	4	6FT [1.8M]																																
1300130536	1R5007A20F030	5	3FT [0.9M]																																
1300131009	1R6007A20F030	6	3FT [0.9M]																																
1 WHITE 2 BLACK	1 GREEN/YELLOW 2 BLACK 3 WHITE	1 BLACK 2 WHITE 3 RED 4 GREEN/YELLOW	1 WHITE 2 RED 3 GREEN/YELLOW 4 ORANGE 5 BLACK	1 WHITE 2 RED 3 GREEN/YELLOW 4 ORANGE 5 BLACK 6 BLUE																															

NOTES:

1. MATERIAL: AS NOTED

2. FINISH: AS NOTED

3. ELECTRICAL:

VOLTAGE: 2P & 3P: 500V PER IEC60664

4P: 483V PER IEC60664

5P & 6P: 400V PER IEC60664

600V PER UL2238

CURRENT: 2P & 3P: 13A

4P: 10A

5P & 6P: 8A

4. TEMP RATING: -20°TO +105°C

5. PROTECTION: IP67 (WHEN MATED)


6. UL RECOGNIZED FILE: E152210

CSA CERTIFIED FILE: LR6837

7. ALL DIMENSIONS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

6	FLAG LABEL	VINYL	BLACK/YELLOW
5	POTTING MATERIAL	EPOXY	
4	WIRE 16AWG (UL1015)	PVC INSULATION	SEE CHART
3	CONTACT PIN	COPPER ALLOY	GOLD OVER NICKEL
2	MALE INSERT	TPE	YELLOW
1	RECEPTACLE SHELL	ZINC DIE-CAST	BLACK E-COAT
ITEM	DESCRIPTION	MATERIAL	FINISH

DOCUMENT STATUS	P1	RELEASE DATE	2022/06/14	13:48:37
-----------------	----	--------------	------------	----------



FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												
	DIMENSION UNITS		SCALE		CURRENT REV DESC: 2P VOLTAGE WAS 600V. MODIFIED TEMP RATING & PN TABLE. ADDED WIRE STRIP END.			molex					
	INCH/MM		NTS										
	GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 709714 DRWN: ABENJAMINLW 2022/02/18 CHK'D: RSTONE 2022/06/08 APPR: BWOODMAN 2022/06/14			MINI-CHANGE RECEPTACLE, A SIZE 2-6 POLE, MALE, 90DEG, SINGLE KEY, #16 AWG					
DIVISIONAL SYMBOLS			mm	INCH	INITIAL REVISION: DRWN: RSTONE 2019/03/27 APPR: BWOODMAN 2019/03/30			PRODUCT CUSTOMER DRAWING					
	4 PLACES	±----	±----	±----				DOCUMENT NUMBER					
	3 PLACES	±----	±----	±----				SD-130013-090					
	2 PLACES	±----	±----	±----				DOC TYPE DOC PART REVISION					
	1 PLACE	±----	±----	±----				PSD 001 B1					
DIVISIONAL SYMBOLS	0 PLACES	±----	±----	±----	THIRD ANGLE PROJECTION			MATERIAL NUMBER					
	ANGULAR TOL ± ---- °							CUSTOMER					
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS							SHEET NUMBER					
						DRAWING		SERIES					
						C-SIZE		130013					
								SEE CHART		GENERAL MARKET			
										1 OF 1			