



MALE FACE VIEW	
3-POLE	4-POLE
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK

POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
3	1200880042	503006A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]
3	1200880044	503006A10M050	16.40' +6.50" -0 [5.0M +165.1 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-20°C TO 105°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	SLEEVE INSERT	PA	
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	SNAP SLEEVE	BRASS	NICKEL PLATED
4	OVERMOLD	TPE	YELLOW
5	CABLE- 24 AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET: PVC	YELLOW

DOCUMENT STATUS	Product Release	RELEASE DATE	2025-08-11	####
-----------------	-----------------	--------------	------------	------

FUNCTIONAL SYMBOLS <
--