ATGBICS

ATGBICS MFS1S00-V010E NVIDIA Mellanox Compatible Active Optical Cable 200GBase QSFP56 (850nm MMF 10m)



Brand : ATGBICS

Product code: MFS1S00-V010E-C

Product name : MFS1S00-V010E NVIDIA Mellanox Compatible Active Optical Cable 200GBase QSFP56 (850nm MMF 10m)

MFS1S00-V010E NVIDIA Mellanox Compatible Active Optical Cable 200GBase QSFP56 (850nm MMF 10m)

ATGBICS MFS1S00-V010E NVIDIA Mellanox Compatible Active Optical Cable 200GBase QSFP56 (850nm MMF 10m):

ATGBICS NVIDIA Mellanox Compatible MFS1S00-V010E 200GBase QSFP56 to QSFP56 Active Optical Cable operates over Active Fibre using a wavelength of 850nm over MMF with a cable length of 10m. This product operates within a commercial temperature range. It is suitable for short reach connection between two QSFP56 ports in 200G interconnecting networking applications. Our product meets the specification of NVIDIA Mellanox MFS1S00-V010E and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.
ATGBICS MFS1S00-V010E NVIDIA Mellanox Compatible Active Optical Cable 200GBase QSFP56 (850nm MMF 10m). Cable length: 10 m, Cable type: AOC, Connector 1: QSFP56, Connector 2: QSFP56

Features	
Cable length *	10 m
InfiniBand protocol	✔
Cable shape	Round
Fastening type	Push–pull
Connector 1 *	QSFP56
Connector 2 *	QSFP56
Connector 1 gender *	Male
Connector 2 gender *	Male
Cable type *	AOC
Product colour *	Aqua colour, Orange
Wavelengths supported	850 nm
Ethernet interface type	200 Gigabit Ethernet
Data transfer rate	200000 Gbit/s
Data transfer rate	200000 Mbit/s
Jacket material *	Optical fiber non-conductive plenum (OFNP), Low smoke zero halogen (LSZH)
Brand compatibility	Nvidia

Features	
Plug and Play	✔
Sustainability	
Doesn't contain	Lead
Certificates	
Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Certification	CE, FCC, RoHS, REACH, FDA, TUV
Operational conditions	
Operating temperature (T-T)	0 - 70 °C
Storage temperature (T-T)	-40 - 85 °C
Weight & dimensions	
Bending radius	3 cm
Packaging content	
Quantity per pack	1 pc(s)
Other features	
Networking standards	IEEE 802.3cd
Logistics data	
Country of origin	China

Catalog Object Cloud

Publication date: 19-JUL-2026. Prints or copies of Information are only valid on the printed Publication date