



Powering Business Worldwide

TRIPP LITE  
SERIES

## Serial ATA (SATA) Right-Angle Signal Cable (7Pin/7Pin-Down), 19-in. (48.26 cm)

MODEL NUMBER: **P942-19I**

### Features

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Support data transfer rates of up to 6.0 Gbps
- Narrow cables design: 1) simplifies cable routing and installation 2) improves air flow within CPU (no more big ribbons blocking air movement)
- Meets Serial ATA 1.0 standards, including Errata 029
- Cable is shielded to protect against EMI/RFI

### Highlights

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Features 7Pin Straight and 7Pin Right-Angle Down connectors
- Angled connector ideal for situations in which space is at a premium, and reduces stress / excessive bending on the cable
- SATA III (6Gbps) / SATA II (3Gbps) / SATA I (1.5Gbps) Compliant
- Cable is shielded to protect against EMI/RFI

### Applications

- Connect your high-speed Serial ATA device to a Serial ATA controller
- Compatible with Serial ATA Hard Drives, Blu-ray/DVD/CD Drives and other Serial ATA devices

### System Requirements

- Serial ATA device
- Serial ATA controller

### Package Includes

- 19-in. Serial ATA Right Angle (SATA) Signal Cable 7Pin/7Pin, Straight/Down

## Specifications

| OVERVIEW             |                                      |
|----------------------|--------------------------------------|
| UPC Code             | 037332120076                         |
| Technology           | SATA/eSATA                           |
| CONNECTIONS          |                                      |
| Side A - Connector 1 | 7 PIN SATA (MALE)                    |
| Side B - Connector 1 | 7 PIN SATA (MALE) - RIGHT ANGLE DOWN |
| PHYSICAL             |                                      |
| Color                | Red                                  |
| Cable Jacket Color   | Red                                  |
| Wire Gauge (AWG)     | 26                                   |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                           |
|-------------------------------------|---------------------------|
| Cable Length (ft.)                  | 1.6                       |
| Cable Length (m)                    | 0.49                      |
| Cable Length (in.)                  | 19                        |
| Cable Length (cm)                   | 48.26                     |
| Shipping Dimensions (hwd / in.)     | 5.30 x 3.90 x 0.50        |
| Shipping Dimensions (hwd / cm)      | 13.46 x 9.91 x 1.27       |
| Shipping Weight (lbs.)              | 0.14                      |
| Shipping Weight (kg)                | 0.06                      |
| FEATURES & SPECIFICATIONS           |                           |
| IP68 Rated                          | No                        |
| IP20 Rated                          | No                        |
| STANDARDS & COMPLIANCE              |                           |
| Product Compliance                  | RoHS                      |
| WARRANTY & SUPPORT                  |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.