



REPRESENTATIVE IMAGE


Product: [2824RW](#) 

Indoor/Outdoor Stadium Cable, 3-Channel SMPTE, 6 Fiber, 6 Conductor 18 AWG, 6 Conductor 24 AWG, CPE Jacket

Product Description

Indoor/Outdoor, 3-Channel SMPTE Stadium Cable, 6 Single Mode Fibers, 6 TC Conductor 18 AWG (19x30) and 6 TC Conductor 24 AWG (7x32), Beldfoil Shields, Water Blocking Tape, CPE Jacket

Technical Drawing



Technical Specifications

Product Overview

Product Category:	SMPTE Cable
Suitable Applications:	3 Channel Composite Camera Cable

Fiber Specifications

Fiber Type:	OS2, G.657.A2
Fiber Buffer Material:	PVC - Polyvinyl Chloride
Fiber Buffer Diameter:	900 µm
Fiber Count:	6
Fiber Color Code:	Yellow Printed

Fiber Construction

Subunit Waterblocking:	Aramid Yarn
Fibers Per Subunit:	1

Conductor Specifications

Conductor Size:	24 AWG, 18 AWG
Insulation Material:	PVC

Outer Jacket Specifications

Optical Characteristics

Wavelength	1310 nm	1550 nm
Max. Attenuation	0.50 dB/km	0.50 dB/km

Mechanical Characteristics

Bulk Cable Weight:	134 lbs/1000ft (199 kg/km)
--------------------	----------------------------

Temperature Range

Operating Temperature Range:	-40°C to 70°C
Installation Temperature Range:	-10°C to 70°C
Storage Temperature Range:	-40°C to 70°C

Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor, Outdoor
Flammability / Reaction to Fire:	UL1666 Vertical Shaft
NEC / UL Compliance:	CMR
CEC / C(UL) Compliance:	.
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

Product Notes

Notes:	Copper conductor quads are individually shielded with individual drain wire
--------	---

History

Update and Revision:	Revision Number: 0.147 Revision Date: 09-07-2025
----------------------	--

Part Numbers

Variants

Item #	Put-Up Type	Length	UPC
2824RW 005CUT	Reel		
2824RW 0051000	Reel	1,000 ft	612825400066
2824RW 0055000	Reel	5,000 ft	612825400073

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.