


Socket, PCB terminals, screened, 2-pole, Audio Plug/Sockets, 6.3 mm



See below:

Approvals and Compliances

Description

- PCB :
Screw-on mounting , rear-side
- Audio entrances and exits
- Data and Signal transfer
- Audio Plug: 2-pole , shielded , straight

References

Alternative: Housing insulated 4833.2200

Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

Diameter	6.3 mm	Allowable Operation Temperature	-20 °C to 70 °C
Number of Poles	2-pole	Terminal	PCB terminals tin-plated
Ratings DC	1 A / 30VDC	Mounting	Screw-on mounting wall thickness max. 4.0mm
Ratings AC	1 A / 30VAC	Housing	screened
Dielectric Strength	500VDC	Style	straight
Insulation Resistance	> 50 MΩ @ 500VDC	Lifetime	5000 Insertions

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

Diagram illustrating a two-channel system. The top channel has a triangle pointing right, labeled S1 and F1. The bottom channel has a triangle pointing left, labeled F2 and S2.

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Audio Plug/Socket	6.3	2-pole	PCB terminals	4833.2220

Packaging unit	100 Pcs
-----------------------	---------

Plug, solder terminal, screened, 2-pole, Audio Plug/Sockets, 6.3 mm	4833.1200
Plug, solder terminal, insulated, 2-pole, Audio Plug/Sockets, 6.3 mm	4833.1220