


REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A4	PART STATUS CHANGE TO DISCONTINUNACE	25JUN2026	NS	PS

1. MATERIAL:
HOUSING: POLYAMIDE 6 UL94V-0.
COLOR: BROWN.
TUBULAR CONTACT: BRASS, TIN PLATED.
SCREW: M5, STEEL, ZINC PLATED W/ NON-HEXAVALENT CHROMATE (CHROME III).
WIRE PROTECTOR: STAINLESS STEEL
2. ELECTRICAL:
CURRENT RATING: 65A, 600V.
WIRE RANGE: 6-14 UL AND 6-22 AWG FOR (CSA)
3. CONTINUOUS WORKING TEMP.: 150°C MAX.
- 4 CUTTING PROJECTION CAN BE ON BOTH SIDES
DEPENDING ON CUTTING LOCATION.
5. CUTTING BURR MAX. 1mm ALLOWED.



	145.0	170.7	TSB2000K12DSHT	1-1986469-2
OBSOLETE	130.5	156.2	TSB2000K11DSHT	1-1986469-1
OBSOLETE	116.0	141.7	TSB2000K10DSHT	1-1986469-0
OBSOLETE	101.5	127.2	TSB2000K09DSHT	1986469-9
	87.0	112.7	TSB2000K08DSHT	1986469-8
OBSOLETE	72.5	98.2	TSB2000K07DSHT	1986469-7
	58.0	83.7	TSB2000K06DSHT	1986469-6
	43.5	69.2	TSB2000K05DSHT	1986469-5
	29.0	54.7	TSB2000K04DSHT	1986469-4
	14.5	40.2	TSB2000K03DSHT	1986469-3
	-	25.7	TSB2000K02DSHT	1986469-2
OBSOLETE	-	11.2	TSB2000K01DSHT	1986469-1
	DIM B	DIM A	CATALOG NUMBER	TE PART NUMBER

1986469-4 AS SHOWN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S SCHLEGEL 9/17/08	TE Connectivity		
		CHK C RICHARD 9/17/08			
DIMENSIONS: mm		APVD C RICHARD 9/17/08	NAME 14.5MM PITCH WIRE PROTECTOR 65A HIGH VOLTAGE VERSION, HIGH TEMP		
		PRODUCT SPEC			
		APPLICATION SPEC			
MATERIAL SEE NOTES		WEIGHT -	SIZE A3	CAGE CODE 00779	DRAWING NO C-1986469
			RESTRICTED TO -		
			SCALE NTS	SHEET 1 OF 1	REV A4