


1. THE CONTACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT.

△ MATERIAL:

HOUSING & COVER - THERMOPLASTIC, BLACK.
TERMINALS - PHOS BRONZE PLATED WITH EITHER .000050 MINIMUM GOLD PLATE, OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000050 MIN TOTAL ON MATING SURFACE. GOLD FLASH PLATED ON TERMINATING SIDE. .000050 MINIMUM NICKEL UNDERPLATE OVER ENTIRE TERMINAL.

- △ COVER SHOWN LOOSE BUT SHIPPED ASSEMBLED.

4. WIRE RANGE: 26 AWG SOLID THRU 30 AWG SOLID AND 28 AWG STRANDED RIBBON CABLE.

- △ ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY UNLESS OTHERWISE SPECIFIED.

- △ FLAT CABLE SHALL BE FURNISHED BY CUSTOMER.

- △ MATING FACE CONSISTS OF TWO ROWS OF TERMINALS ON .085 CENTERS. TERMINATING SIDE CONSISTS OF TERMINALS ON .100 CENTERS FOR AN EFFECTIVE .050 TERMINATION.

- △ PANEL THICKNESS RANGE:

FRONT PANEL MOUNTING - .125 MAX
REAR PANEL MOUNTING - .062 MAX

9. FOR MORE INFORMATION REFER TO AMP PRODUCT SPECIFICATION 108-6076 & APPLICATION SPEC 114-6030.

.620	.310	.149	1.575	REAR PANEL MOUNTING
.640	.320	.126	1.488	FRONT PANEL MOUNTING
DIM D	DIM C	DIM B	DIM A	DESCRIPTION

SUGGESTED PANEL CUTOUT △

THIS DRAWING IS A CONTROLLED DOCUMENT:		REV. 19/AMX/07		TPO Electronics Corporation Harrisburg, PA 17105-5088	
DATE: 01/01/07		BY: W. MILLIKENS		17/AMX/07	
DRAWN BY: J. R. C.		CHECKED BY: J. R. C.		APPROVED BY: J. R. C.	
PRODUCT SPEC: RECEPTACLE ASSEMBLY, 24 POSITION PANEL MOUNTING, LDM PROFILE, CHAMP LATCH		APPLICATION SPEC: -		SHEET: 1 OF 1	
CUSTOMER DRAWING: A2100779		REV: 554088		REV: G	