





REVISIONS					
P	LTR	DESCRIPTION		DATE	OWN APVD
	C3	REVISED PER ECN-26-390651		25JUN2026	NG SVN




ITEM	MATERIAL	FINISH
①	COPPER ALLOY	NICKEL UNDER PLATE ALL OVER CONTACT AREA ; Au(0.3u, 0.76u) SOLDER TINE AREA ; TIN PLATE
②	ZINC	NICKEL PLATING
③	STEEL t0.25	NICKEL PLATE OVER COPPER UNDERPLATE
④ ⑤	THERMO-PLASTIC(UL:94V-0)	COLOR; BLACK
⑥	COPPER ALLOY	TIN PLATE OVER NICKEL UNDERPLATE

NOTES:

- ⚠ RECOMMENDED SCREW SIZE ; M2.6 PANHEAD SCREW(L=5)
2. RECOMMENDED P.C BOARD THICKNESS ; 1.6mm (REF)
3. CONNECTOR TO BE MATED;175677
4. INSERTION FORCE OF RETENTION LEG TO P.C.B; 21.56N(2.2kgf) MAX/CONNECTOR.
5. RETENTIVITY OF RETENTION LEG TO P.C.B; 4.9N(0.5kgf) MIN/CONNECTOR.
⚠ ALTERNATE CONTACT PLATING: Au 2u”+30u” PdNi



RECOMENDED PANEL CUTOUT
THK,2mm MAX



RECOMMENDED PC BOARD
MOUNTING DIMMENSION
(COMPONENT SIDE)

LEAD FREE

OBSOLETED	-39	61.9	61.55	71.45	65.55	54.53	49.53	0.76um	80	3-5178238-0
OBSOLETED	-49	74.6	74.25	84.15	78.25	67.23	62.23	0.76um	100	2-5178238-9
OBSOLETED	-33	54.2	53.93	63.83	57.93	46.91	41.91	0.76um	68	2-5178238-8
OBSOLETED	-24	42.8	42.50	52.40	46.50	35.48	30.48	0.76um	50	2-5178238-7
OBSOLETED	-17	33.9	33.61	43.51	37.61	26.59	21.59	0.76um	36	2-5178238-5
	12	27.6	27.26	37.16	31.26	20.24	15.24	0.76um	26	2-5178238-4
OBSOLETED	-9	23.8	23.45	33.35	27.45	16.43	11.43	0.76um	20	2-5178238-2
	6	19.9	19.64	29.54	23.64	12.62	7.62	0.76um	14	2-5178238-1
OBSOLETED	-39	61.9	61.55	71.45	65.55	54.53	49.53	0.3 um	80	1-5178238-0
OBSOLETED	-49	74.6	74.25	84.15	78.25	67.23	62.23	0.3 um	100	5178238-9
OBSOLETED	-33	54.2	53.93	63.83	57.93	46.91	41.91	0.3 um	68	5178238-8
	24	42.8	42.50	52.40	46.50	35.48	30.48	0.3 um	50	5178238-7
OBSOLETED	-17	33.9	33.61	43.51	37.61	26.59	21.59	0.3 um	36	5178238-5
	12	27.6	27.26	37.16	31.26	20.24	15.24	0.3 um	26	5178238-4
	9	23.8	23.45	33.35	27.45	16.43	11.43	0.3 um	20	5178238-2
	6	19.9	19.64	29.54	23.64	12.62	7.62	0.3 um	14	5178238-1
	N	F	E	D	C	B	A	Au PLT.	POSITION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.				DWN T.KAWAMAE 13DEC04		 TE Connectivity									
				CHK I.ENOMOTO 13DEC04											
DIMENSIONS: mm		TOLERANCES, UNLESS OTHERWISE SPECIFIED:		APVD I.ENOMOTO 13DEC04		NAME									
		0 PLC ± 0.2		PRODUCT SPEC		RECEPTACLE HDR ASSY (3.1mm) RETENTION LEG TYPE STANDARD CHAMP.050 SERIES (II)									
		1 PLC ± 0.2		108-5288											
		2 PLC ± 0.2		APPLICATION SPEC											
		3 PLC ± 0.2		WEIGHT 0.000000											
		4 PLC ± 0.2													
ANGLES ± 3°				SIZE		CAGE CODE		DRAWING NO		RESTRICTED TO					
MATERIAL SEE TABLE		FINISH SEE TABLE		A2		00779		C=5178238		—					
CUSTOMER DRAWING						SCALE		2:1		SHEET		1 of 1		REV C3	