



DESCRIPTION: 0.900 CENTER DUAL PORT D-SUB - MALE OVER MALE

25 PIN
SHOWN



SPECIFICATIONS:

MATERIALS:

HOUSING:	UL94 V-0 RATED, BLACK PA9T, 260° PROCESS TEMP.
CONTACTS:	GOLD PLATED BRASS (SEE P/N KEY BELOW)
SHELL:	NICKEL PLATED STEEL

ELECTRICAL:

RATED CURRENT:	5A
INSULATOR RESISTANCE:	1,000 Ohms MIN.
DIELECTRIC STRENGTH:	1,000 VAC RMS
WORKING VOLTAGE:	250V
OPERATING TEMPERATURE:	-55°C TO +105°C

DIMENSIONS:				
	9	15	25	37
A	1.204 [30.58]	1.535 [38.99]	2.078 [52.78]	2.724 [69.19]
B	0.984 [24.99]	1.312 [33.32]	1.850 [46.99]	2.500 [63.50]
C	0.494 [12.55]	0.494 [12.55]	0.494 [12.55]	0.494 [12.55]

179-YYY-613R451

SERIES	
POSITIONS	
009	
015	
025	
037	
GENDER	
31 = FEMALE OVER MALE	
41 = MALE OVER FEMALE	
51 = FEMALE OVER FEMALE	
61 = MALE OVER MALE	
SHELL PLATING	
3 = NICKEL	
HARDWARE OPTIONS	
45 = 4-40 INSERTS/METAL BRACKET	
PLATING OPTIONS	
1 = SELECTIVE (GF MATING AREA / TIN PLATED TAILS)	
A = 30u" GOLD MATING AREA/GOLD FLASH TAILS	
9 = 30u" GOLD MATING AREA/TIN TAILS	

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

C. SMITH

DATE:

03/30/07

NorComp

SCALE:
NTS

SHEET OF
1 1

REV
6

DWG NO.

179-YYY-613R451