


D

C

B

A



- 1
- MATERIAL:
BACK INSULATOR: PBT, 30 %GF, UL94V-0, BLACK COLOR
FRONT INSULATOR: PBT, 30 %GF, UL94V-0, BLACK COLOR
CONTACT: BRASS
BACK SHELL: STEEL
CLINCH NUTS: BRASS
FRONT SHELL: STEEL
- 2
- FINISH:
CONTACT: GOLD PLATING 0.00002[.0000008] MIN ON CONTACT AREA 0.00229 [.000090] MIN TIN-LEAD PLATING ALL OVER 0.00127[.000050] MIN NICKEL
- 3
- CONTACT: GOLD PLATING 0.00076[.000030] MIN ON CONTACT AREA 0.00229 [.000090] MIN TIN-LEAD PLATING ALL OVER 0.00127[.000050] MIN NICKEL
- 4
- SHELL: BRIGHT TIN 0.00241[.000095] MIN FULL SHELL
- 5
- SHELL: BLUE ZINC: 0.00508[.000200] - 0.00762[.000300] OVER ENTIRE SHELL
- 6
- CONTACT: GOLD PLATING 0.00002[.0000008] MIN ON CONTACT AREA 0.00229 [.000090] MIN HOT DIPPED TIN-COPPER PLATING ALL OVER 0.00127[.000050] MIN NICKEL.
- 7
- CLINCH NUTS: NICKEL PLATING .00305-.00508[.000120-.000200]
- 8
- SPECIFICATION
ELECTRICAL CHARACTERISTICS: CURRENT RATING: 3 AMPERES
DIELECTRIC WITHSTANDING VOLTAGE: AC 1000V r.m.s
INSULATION RESISTANCE: 5000 MEGOHMS MINIMUM AT DC 500V
CONTACT RESISTANCE: 10 MILLIOHMS MAXIMUM.
- 9
- ROHS 2002/95/EC COMPLIANT
- 10
- RECEPTACLE ASSEMBLY MATES WITH ANY 15 POSITION PLUG IN AMPLIMITE SERIES
- 11
- SOLDER CUP WILL ACCOMMODATE 20 MAX AWG WIRE.
- 12
- CONTACT: GOLD PLATING 0.00076[.000030] MIN ON CONTACT AREA 0.00229[.000090] MIN HOT DIPPED TIN-COPPER ALL OVER 0.00127[.000050] MIN NICKEL PLATING

D

C

B

A

9	OBSOLETE	STANDARD	NO	6	5	5-747909-4
9	OBSOLETE	STANDARD	YES	6	4	5-747909-7
9		STANDARD	NO	2	4	5-747909-5
9		STANDARD	NO	6	4	5-747909-2
	SUPERSEDED TO 5-747909-2	STANDARD	NO	6	4	747909-8
	SUPERSEDED TO 5-747909-7	STANDARD	YES	2	4	747909-7
	SUPERSEDED TO 5-747909-5	STANDARD	NO	3	4	747909-5
	SUPERSEDED TO 5-747909-4	STANDARD	NO	2	5	747909-4
	SUPERSEDED TO 5-747909-2	STANDARD	NO	2	4	747909-2
		PACKAGING TYPE	CLINCH NUTS	CONTACTS	SHELLS	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		DWN M.BINNER 03MAR03	TE Connectivity			
DIMENSIONS: mm [INCHES]		CHK R.BENDORF 05MAR03				
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± 0.25 2 PLC ± 0.13 3 PLC ± 0.05 4 PLC ± - ANGLES ± 4°		APVD R.BENDORF 05MAR03	NAME RECEPTACLE ASSEMBLY, SOLDER CUP, SIZE 2, 15 POSN, HD-20, AMPLIMITE			
MATERIAL 1		PRODUCT SPEC -	-			
FINISH SEE TABLE		APPLICATION SPEC -	-			
		WEIGHT -	SIZE A2	CAGE CODE 00779	DRAWING NO C=747909	RESTRICTED TO -
		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 of 1	REV Z	