





REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	PART STATUS CHANGE TO DISCONTINUANCE	10JUN2026	NS	PS



RECOMMENDED PC BOARD LAYOUT

NOTES :

1. MATERIAL AND FINISH :
HOUSING : HIGH TEMPERATURE POLYAMIDE UL94 V0
HOUSING COLOR : BLACK
TERMINAL : COPPER ALLOY ,TIN PLATED OVER NICKEL UNDERPLATED.
2. ELECTRICAL PROPERTIES:
RATED VOLTAGE: 300V
RATED CURRENT: 11A
CONTACT RESISTANCE : <15 m Ohm
INSULATION RESISTANCE : >1000 M Ohm (500V DC)
3. NOT CUMULATIVE TOLERANCE
4. MECHANICAL PROPERTIES:
RECOMENDED PCB THICKNESS : 1.6mm-2.4mm
WIRE STRIPPING LENGTH : 6mm
5. OPERATING TEMPERATURE RANGE : -40°C TO +105°C.
6. NOTE DELETED
7. PACKAGING:BULK PACKING AS PER 107-160052
8. PACKAGING:T & R PACKING AS PER 107-160194

	TAPE & REEL	3.4	22.0	6	1-1776134-6
OBSOLETE	TAPE & REEL	2.6	18.5	5	1-1776134-5
OBSOLETE	TAPE & REEL	2.6	11.5	3	1-1776134-3
OBSOLETE	BULK	3.4	43.0	12	1-1776134-2
OBSOLETE	BULK	3.4	39.5	11	1-1776134-1
	BULK	3.4	36.0	10	1-1776134-0
OBSOLETE	BULK	3.4	32.5	9	1776134-9
	BULK	3.4	29.0	8	1776134-8
OBSOLETE	BULK	3.4	25.5	7	1776134-7
	BULK	3.4	22.0	6	1776134-6
	BULK	3.4	18.5	5	1776134-5
OBSOLETE	BULK	3.4	15.0	4	1776134-4
	BULK	3.4	11.5	3	1776134-3
	BULK	3.4	8.0	2	1776134-2
	PACKAGING	DIM B	DIM A	NO. OF POS.	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. SCHLEGEL CHK C. RICHARD APVD C. RICHARD	05JAN2010 05JAN2010 05JAN2010	TE Connectivity	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±0.3 2 PLC ±0.25 3 PLC ±- 4 PLC ±- ANGLES ±2°	PRODUCT SPEC 108-161088	NAME TERMINAL BLOCK HEADER, 90 DEGREE, CLOSED ENDS, 3.5mm PITCH	SIZE A2	CAGE CODE 00779
MATERIAL 1	FINISH 1	APPLICATION SPEC 114-20079	DRAWING NO C-1776134	RESTRICTED TO -	SCALE 6:1
CUSTOMER DRAWING			SHEET 1 OF 1	REV A2	