

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOC

DIST

REV

DATE

DWN

APVD

FT

0

A1

CORRECTION OF PCB MOUNT VIEW

19JUN2015

NV

PS

HEADER:

MATERIALS:

HEADER: COPPER ALLOY, GOLD PLATED, 94V-0 THERMOPLASTIC.

CONNECTOR: COPPER ALLOY, GOLD PLATED, 94V-0 THERMOPLASTIC.

ELECTRICAL:

RATING: 1 AMPERE MAX. (CONNECTOR).

MECHANICAL:

WIRE RANGE: 26-30 AWG SOLID, 28 AWG STRANDED.

TERMINAL BLOCK:

MATERIALS:

HOUSING: THERMOPLASTIC NYLON, BLACK, 94V-0.

TERMINALS: COPPER ALLOY, TIN PLATED.

SCREWS: 3M, BRASS, NICKEL PLATED.

ELECTRICAL:

RATING: 10A, 300V(UL).

MECHANICAL:

WIRE RANGE: 14-22 AWG.

MOUNTING:

MATERIALS:

MOUNTING: 2TK2 AND 2TK2D SERIES SNAPTRACK (SOLD SEPARATELY).

1 ALL CONNECTOR/STRAIN RELIEF COMPONENTS TO BE SHIPPER LOOSE AND UNASSEMBLED.

2 CATALOG NUMBER MARKED HERE.

3 CONTAINS NO TIN-LEAD PLATING.

4.70

LOGO AREA

2M40FC

2

40

1

39

.7

.06

2.75

0.6

0.10 MAX

1

1

3

5

7

9

11

13

15

17

19

21

23

25

27

29

31

33

35

37

39

1

1

3

5

7

9

11

13

15

17

19

21

23

25

27

29

31

33

35

37

39

1

1

3

5

7

9

11

13

15

17

19

21

23

25

27

29

31

33

35

37

39

4805 (3/11)