



ebm-papst St. Georgen GmbH & Co. KG
Hermann-Papst-Str. 1
D-78112 St. Georgen
Phone +49 (0) 7724 81-0
info2@de.ebmpapst.com
www.ebmpapst.com

Nominal data

Item	3906 L	
Motor	-0	
Phase		1~
Nominal voltage	VAC	115
Frequency	Hz	60
Speed (rpm)	min ⁻¹	1850
Power consumption	W	5.0
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	80
Air flow	m ³ /h	39
Sound power level	B	4.0
Sound pressure level	dB(A)	27

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Technical description

Weight	0.280 kg
Dimensions	92 x 92 x 25 mm
Impeller material	Mineral-reinforced PA plastic
Housing material	Die-cast aluminum
Airflow direction	Exhaust over struts
Service life L10 at 40 °C	70000 h
Service life L10 at maximum temperature	27500 h

Technical drawing of a square fan with dimensions:

- Top left dimension: $25,4 \pm 0,3$
- Top right dimension: 4
- Right side dimension (inner): $82,5 \pm 0,2$
- Right side dimension (outer): $82,5 \pm 0,2$
- Right side dimension (total): 88
- Bottom right dimension (inner): $4,5 \pm 0,2$
- Bottom right dimension (outer): $4,3 \pm 0,15$
- Bottom right dimension (total): (6x)
- Bottom left dimension: $92 \pm 0,3$
- Center hole dimension: $\varnothing 98$

Curves: Air performance

