

Product data sheet

Specifications



ferrite suppressors for downstream contactor opening

VW3A31453

⚠ Discontinued on: Aug 15, 2025

⚠ To be discontinued

Main

Product or component type	Ferrite suppressors for downstream contactor opening
Range compatibility	Altivar 312 Altivar 312 Solar Altivar 12
Product specific application	Output filter
compatibility with variable speed drives	Variable speed drive ATV12H at 0.55 kW, 200...240 V, single phase Variable speed drive ATV12H at 0.75 kW, 200...240 V, single phase Variable speed drive ATV12H at 1.5 kW, 200...240 V, single phase Variable speed drive ATV12H at 2.2 kW, 200...240 V, single phase Variable speed drive ATV12H at 0.75 kW, 200...240 V, three phase Variable speed drive ATV12H at 1.5 kW, 200...240 V, three phase Variable speed drive ATV12H at 2.2 kW, 200...240 V, three phase Variable speed drive ATV312 at 0.55 kW, 200...240 V, single phase Variable speed drive ATV312 at 0.75 kW, 200...240 V, single phase Variable speed drive ATV312 at 1.1 kW, 200...240 V, single phase Variable speed drive ATV312 at 1.5 kW, 200...240 V, single phase Variable speed drive ATV312 at 2.2 kW, 200...240 V, single phase Variable speed drive ATV312 at 0.55 kW, 200...240 V, three phase Variable speed drive ATV312 at 0.75 kW, 200...240 V, three phase Variable speed drive ATV312 at 1.1 kW, 200...240 V, three phase Variable speed drive ATV312 at 1.5 kW, 200...240 V, three phase Variable speed drive ATV312 at 2.2 kW, 200...240 V, three phase
Sale per indivisible quantity	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.500 cm
Package 1 Width	16.000 cm
Package 1 Length	14.000 cm
Package 1 Weight	154.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.480 kg
Unit Type of Package 3	P06
Number of Units in Package 3	56

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	21.844 kg

Contractual warranty

Warranty	18 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No