



Wire guard
(accessory)



Adaptor for tube mounting
and plastic bracket
(accessories)

- High flash power from two consecutive flashes
- High light intensity
- Adaptor for tube mounting (accessory)
- High impact resistance to 20 Joules



TECHNICAL SPECIFICATIONS:

Dimensions (Ø x Height):	142 mm x 218 mm
Housing:	PC/ABS-Blend
Lens:	PC, transparent
Fixing:	Base mounting, Bracket mounting (accessory), Tube mounting (accessory)
Connection:	Screw terminal with wire protection 2.5 mm ²
Cable entry:	Cable diameter 5-7 mm
Flash energy:	15 Ws
Flash frequency:	C. 1 Hz
Power supply frequency:	50/60 Hz
Life duration:	4 x 10 ⁶ flashes



ORDER SPECIFICATIONS:

Voltage	24 V DC	115 V AC	230 V AC
Current consumption:	800 mA	400 mA	200 mA
red	838 100 55	838 100 67	838 100 68
yellow	838 300 55	838 300 67	838 300 68



ACCESSORIES:

Plastic bracket for wall mounting	975 883 06
Adaptor for tube mounting	975 883 09
Wire guard, only for base mounting	975 883 08



TECHNICAL DIAGRAMS:

see page 317

Sizes of Flashing Beacons



See note
on page 347

